TRIM® TC 155

Nonferrous Corrosion Inhibitor

TRIM TC 155 is a nonferrous corrosion inhibitor for use in water soluble and straight oil systems. It is particularly effective in preventing staining and white rust on die cast alloys containing copper.

Additives



The troubleshooters:

As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.

Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.

Choose TC 155:

- Prevents staining and white rust on die cast alloys containing copper
- Nonferrous corrosion inhibition

TC 155 especially for:

Applications — corrosion inhibition

Health and Safety

Request SDS

Master Fluid SOLUTIONS®

TRIM® TC 155

Nonferrous Corrosion Inhibitor

Application Guidelines

- TC 155 is added at a rate of 0.05%-0.125% to working solutions.
- This product should not be used in conjunction with systems containing copper or copper amine compounds as part of their formulation or systems to which these compounds have been added.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at https://www.masterfluids.com/na/en-us/distributors/index.php, your District Sales Manager, or call our Tech Line at 1-800-537-3365.

Physical Properties Typical Data

Color (Concentrate)	Amber
Odor (Concentrate)	None
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 226°F



2-quart tip "N" measure®
SKU: TC155-2Q
UPC-12: 641238074113



1-gallon jug
SKU: TC155-1G
UPC-12: 641238009917



5-gallon pail
SKU: TC155-5G
UPC-12: 641238009955



54-gallon drum
SKU: TC155-54G
UPC-12: 641238009962

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=na_en-us_TC155

501 West Boundary Street
Perrysburg, OH 43551-1200
United States
+1 419-874-7902

info@masterfluids.com

masterfluids.com/na/en-us/